

### Electric Chain Hoist Model BC



- Modular, rugged construction for easy service and maintenance
- Meets or exceeds CSA, DIN, and FEM standards
- Proven electric motor with conical rotor and build-in brake with asbestos-free lining
- Upper and lower limit switch
- Build-in overload protection
- Mode of protection IP54 - protected against dust & splashing water
- Complete control equipment "Telemecanique"
- Supply voltages 230, 460, 575vac – 60 Hz

TYPE	RATED LOAD	REEVING	CHAIN d x t	LIFTING HEIGHT *	LIFTING SPEED	HOISTING MOTOR 240 SW/H		TROLLEY SPEED *	TROLLEY MOTOR	PROFILE WIDTH min/max	MIN. CURVE RADIUS	WEIGHT
						kW	ED %					
-	lbs		mm	ft	ft/min	kW	ED %	ft/min	kW	inch	ft	lbs
BC 033M	1,100	1/1	.27 x.87	20	30 / 8	0.9 / 0.3	40 / 10	-	-	-	-	139
BC 053M	1,100	1/1	.27 x.87	20	30 / 8	0.9 / 0.3	40 / 10	-	-	3.54 – 5.12	4.92	163
BC 093M	1,100	1/1	.27 x.87	20	30 / 8	0.9 / 0.3	40 / 10	49	0.15	3.54 – 5.12	4.92	189
BC 043M	2,200	2/1	.27 x.87	10	15 / 4	0.9 / 0.3	40 / 10	-	-	-	-	139
BC 063M	2,200	2/1	.27 x.87	10	15 / 4	0.9 / 0.3	40 / 10	-	-	3.54 – 5.12	4.92	163
BC 103M	2,200	2/1	.27 x.87	10	15 / 4	0.9 / 0.3	40 / 10	49	0.15	3.54 – 5.12	4.92	189

\* - Additional options available.